TÜV SÜD America, Inc., Product Safety Services
1866 New Energy Way, Auburn Hills, MI 48326
Phone: (616) 546-4600

Tramp Metals Test Results

ASTM F2075
Standard Specification for Engineered Wood Fiber for Use as a Playground Safety Surface Under and Around Playground Equipment, Section 4.5 and Section 9

Customer/Participant: Greely Sand & Gravel, Inc. Report Date: 8/3/2026
Main Office Address: 1971 Old Prescott Rd., Greely, ON, CAN K4P 1N6 Test Date: 7/29/2026
All testing performed at location ID: Eganville, ON, CAN Project No.: 721021565-1
Commercial Name of Product: Adventure Playground Mulch Follow-up: ☐ Ref. Job:

4.5 Per 9.4 Tramp Metals

Level – 0in. – 15in.

Quadrant 1		Quadrant 2		Quadrant 3		Quadrant 4	
Pass	Fail	Pass	Fail	Pass	Fail	Pass	Fail
☒	☐	☒	☐	☒	☐	☒	☐

Level – 15in. – 30in.

Quadrant 1		Quadrant 2		Quadrant 3		Quadrant 4	
Pass	Fail	Pass	Fail	Pass	Fail	Pass	Fail
☒	☐	☒	☐	☒	☐	☒	☐

Level – 30in. – 45in.

Quadrant 1		Quadrant 2		Quadrant 3		Quadrant 4	
Pass	Fail	Pass	Fail	Pass	Fail	Pass	Fail
☒	☐	☒	☐	☒	☐	☒	☐

Level – 45in. – 60in.

Quadrant 1		Quadrant 2		Quadrant 3		Quadrant 4	
Pass	Fail	Pass	Fail	Pass	Fail	Pass	Fail
☒	☐	☒	☐	☒	☐	☒	☐

Pass ☒ Fail ☐

Comments:

The results reported herein reflect the performance of the above described samples at the time of testing. The results are specific to the described samples. Samples of surfacing materials that do not closely match the described samples will perform differently. This data sheet provides an accurate representation of the test results.
Decision rule for this test is simple acceptance. A measured value is accepted as passing if it falls within the specified tolerance limit.

Performed By: *Timothy Fouchia* Reviewed By:

Title: Project Engineering Technician Title: Regional Manager

Date: 8/3/2026 Date: 8/3/2026